

NEW



T.V. Thermal Valve **T.S.** Total Stop

Heat 1211 LP (Hot water H.P. cleaner)

- 4 poles electrical motor (1450 RPM) with thermal protection. Three pistons, brass linear pump head with built-in by-pass valve.
- Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Low pressure detergent flow with integrated detergent tank (optional).
- Auxiliary motor for burner air-cooling and two ways fuel pump.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Safety valve.
- Panel with analogic controls.
- **Hose reel (optional).**
- **Power led + low diesel light**

code	36078-00033
operating pressure bar max	30÷110 (max 150)
max delivery rate l/h	720
abs. power W/Voltage	3000 - 230V~50Hz
RPM	1450
weight	140 Kg
packing dim.	120 x 74 h 101 cm
pcs for pallet	1

Q.ty: 20'=24 40'=54 40' HC=54

Floor loaded not available.



STANDARD EQUIPMENT



NEW



T.V. Thermal Valve **T.S.** Total Stop

Heat 1515 LP (Hot water H.P. cleaner)

- 4 poles electrical motor (1450 RPM) with thermal protection. Three pistons, brass linear pump head with built-in by-pass valve.
- Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Low pressure detergent flow with integrated detergent tank (optional).
- Auxiliary motor for burner air-cooling and two ways fuel pump.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Safety valve.
- Panel with analogic controls.
- **Hose reel (optional).**
- **Power led + low diesel light**

code	36078-00034
operating pressure bar max	30÷150 (max 180)
max delivery rate l/h	900
abs. power W/Voltage	5500 - 400V~50Hz
RPM	1450
weight	140 Kg
packing dim.	120 x 74 h 101 cm
pcs for pallet	1

Q.ty: 20'=24 40'=54 40' HC=54

Floor loaded not available.



STANDARD EQUIPMENT



NEW



T.V. Thermal Valve **T.S.** Total Stop

Heat 2015 LP (Hot water H.P. cleaner)

- 4 poles electrical motor (1450 RPM) with thermal protection. Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Low pressure detergent flow with integrated detergent tank (optional).
- Auxiliary motor for burner air-cooling and two ways fuel pump.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Safety valve.
- Panel with analogic controls.
- **Hose reel (optional).**
- **Power led + low diesel light**

code	36078-00035
operating pressure bar max	30÷200 (max 210)
max delivery rate l/h	900
abs. power W/Voltage	7300 - 400V~50Hz
RPM	1450
weight	144,5 Kg
packing dim.	120 x 74 h 101 cm
pcs for pallet	1

Q.ty: 20'=24 40'=54 40' HC=54

Floor loaded not available.



STANDARD EQUIPMENT

