

VAC PUMPS ISCOMAT 70 M



FEATURES

Vane rotors



Adjustable bypass valve



On/off switch



Technical Specifications

Model	VISCOMAT 70 M
Code	F0033490A
Flow-Rate	25 l/m
AC Volt / Hz	220 V - 50 Hz
Inlet / Outlet	1"
Power Watt	1150 W
RPM	1470 rpm
Weight	14,1 kg
Dimension	355 x185 x285 mm

المواصفات الفنية

VISCOMAT 70 M	الموديل
F0033490A	الكود
٢٥ لتر / دقيقة	معدل التصريف
٢٢٠ فولت - ٥٠ هرتز	تيار التشغيل
١ بوصة	قطر الدخول والخروج
١١٥٠ وات	القدرة
١٤٧٠ لفة / دقيقة	عدد اللفات
١٤,١ كجم	الوزن
٣٥٥ × ١٨٥ × ٢٨٥ مم	الأبعاد



DISPENSERS



PUMPS



METERS



NOZZLE



FILTRATION

FLUID
MONITORING

VISCOMAT VANE

FEATURES

- VERSATILITY
- MOBILE AND READY TO USE
- MULTIPURPOSE PUMP
- ADJUSTABLE BYPASS

The PIUSI VISCOMAT VANE is an electric vane pump suitable for all those applications where it is necessary to apply a transfer system with high suction capacity in order to transfer fluids with medium-high viscosity up to 500 cSt. The pump is fitted with an asynchronous and self-ventilating motor, closed and available in different voltages and frequencies in order to adapt to any working condition.

PERFORMANCE

UP TO

50 L/MIN

FLOW-RATE

AC

CONTINUOUS DUTY

POWER

UP TO

500 CST

VISCOSITY



VISCOMAT VANE



PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES / EUROPALLET	
	KG	LBS	MM	INCH	PCS/BOX	✈	🚚
VISCOMAT 70							
FO033490A	14,1	31,1	355X185X285	1	1	60	72
FO033190A	14,1	31,1	350X200X280	-	1	60	72
VISCOMAT 90							
FO0303M00	14,1	31,1	350X200X280	-	1	60	72
000303000	14,1	31,1	350X200X280	-	1	60	72



HOSE REELS



ACCESSORIES



MERCHANDISE



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART




IN THE BOX

- VISCOMAT VANE PUMP
- INSTRUCTION MANUAL

DETAILS



ON/OFF SWITCH




VANE ROTOR



ADJUSTABLE BYPASS VALVE

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: CAST IRON
- ROTOR: SINTERED STEEL
- VANES: TECHNOPOLYMER
- SHAFT: STEEL



PUMP

- SUCTION HOSE Ø 1" MIN,
- MAX SUCTION HEIGHT:
 - 2M (7FT) W/O NO BACK VALVE
 - 4M (14FT) W NO BACK VALVE



TANK

TECHNICAL DATA

TECHNICAL DATA														
CODE	DESCRIPTION	FLUIDS TYPE	FLOW-RATE		PRESSURE		VOLTAGE				RPM	INLET/OUTLET BSP	ADJUSTABLE BYPASS VALVE	
			L/MIN	GPM	BAR	PSI	SINGLEPHASE MOTOR V./HZ	THREEPHASE MOTOR V./HZ	POWER WATT	AMP. MAX.				
VISCOMAT 70														
FOO33490A	VISCOMAT 70 M 230/50-60	D O B	25	7	6	85	230/50-60	-	1200/1100	5,5 - 5,1	1470/1650	1"	YES	
FOO33190A	VISCOMAT 70 T 400/50-60	D O B	25	7	6	85	-	400/50 - 400/60	650/1000	2,2 - 3,1	1450/1750	1"	YES	
VISCOMAT 90														
FOO303M00	VISCOMAT 70 M 230/50-60	D O B	50	13	5	71	230/50-60	-	1350/1600	6,2 - 4,9	1400/1600	1"	NO	
OOO303000	VISCOAMT 90 T 400/50	D O B	50	13	5	71	-	400/50	2000	5	1450	1"	YES	

UPON REQUEST IT IS AVAILABLE WITH DIFFERENT VOLTAGE AND FREQUENCY

VISCOMAT VANE