٣) جسم الماكينة صغير مع فرشاة جانبية بارزة وممسحة تدور ٣٠٠ درجة.

٤) يتم إزالة تانك العائد بسهولة بدون استخدام أي أدوات مع نافذة كبيرة

٦) الماكينة محملة على عجلات كبيرة لا تقوم بترك علامات على الأرضية.

للفحض وخرطوم تفريغ مطَّاطي.

٥) مؤشر لبيان مستوى المياه النظيفة.



Walk Behind Compact Floor Scrubber Dryer

3) Narrow body with both side brush protrusion and 300°

4) Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.

Large non making working wheels and sturdy rear roller

squeegee spin.

for displacements.

Clean water tank level indicator.



Technical Specifications	المواصفات الفنية
 Voltage: 230V. Brush motor power / Vacuum motor: 300 W / 350 W. Brush width / Squeegee width: 360 mm / 460 mm. Max Working capacity: 1260 m2/h. Detergent tank capacity: 15 I. Recovery tank capacity: 16 I. Traction: Mechanical. Detergent solution system: Solenoid Valve. RPM / Pressure on the brush: 130 / 18 kg. Dimensions / Weight: 98 x 47 x 99 cm / 57 kg. 	 ١) تيار التشغيل: ٢٣٠ فولت. ٢) قدرة موتور الفرشاة / موتور الشفط: ٣٠٠ واط / ٣٥٠ واط. ٣) عرض الفرشاة / عرض المسحة: ٣٦٠ مم / ٤٦٠ مم. ٤) مساحة العمل: ٢٦٠ م / س. ٥) سعة تانك الإضافات: ١٥ لتر. ٢) سعة تانك العائد: ١٦ لتر. ٧) الجر/ نظام سوائل التنظيف: ميكانيكي / Solenoid Valve. ٨) سرعة الدوران / قوة الضغط على الفرشاة: ٣٠٠ لفة / دقيقة / ١٨ كجم. ٩) الأبعاد / الوزن: ٩٥ × ٤٧ × ٩٥ سم / ٥٧ كجم.
Main Features	مميزات الماكينة
Ideal for small and medium floors up to 1260sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showrooms, retail shops, hospitals and schools. 2 Automatic brush attachment, discharge and delayed cut-off.	 ا مناسبة للأرضيات الصغيرة والمتوسطة تصل إلى ١٢٦٠ متر مربع، خاصة الأماكن المزدحمة بالناس أو الأثاث مثل المراكز الطبية، الصالات الرياضية، معارض السيارات، متاجر التجزئة، المستشفيات، والمدارس. ٢) ديط واذالة الفرشاة أوتومات كياً وخاصية التوقف التلقائي.



Dart















Equipped with:

- Ideal for small and medium floors up to 1260 sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showroom, retail shops, hospitals and schools.
- Li-ion battery 24V (38B Li)
- Automatic brush attachment, discharge and delayed cut-off.
- \bullet Narrow body with both side brush protrusion and 300° squeegee spin.
- Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.
- Adjustable driving handle with dead man switches, soft touch controls and diagnosis (Eco Energy mode and battery low level automatic cut-off for DC version).
- Clean water tank level indicator
- Large non marking working wheels and sturdy rear roller for displacements.

* New, standard on machines starting from 2022, compatible with all previous machine models





- 5.511.2262 PP brush Ø 380 mm - 15" (38 B Li)
- 5.511.2213 PP brush Ø 360 mm - 14" (36 B- 36 E)



• 4.508.1100 Front squeegee blade L.537 mm - Th. 1,5 mm • 4.508.1101 Rear squeegee blade L.590 mm - Th. 3,0 mm



• 0.108.0076 On-board Battery charger 24V-5A only for model code: 8.581.0002 8.581.0003



• 0.108.0089 Onboard Battery charger 29,4V 12A 110-230V 50/60Hz only for model code: 8.581.0022



• 2x 0.107.0083 AGM NP3312 12 V 33 Ah C20/28 Ah C5 (only for model code: 8.581.0003)



• 1x 0.107.0091 Li-ion battery 24V 30Ah 700Wh

only for model code: 8.581.0022

	Dart 36E	Dart 36B	Dart 36B	Dart 38B Li
code	8.581.0001	8.581.0002	8.581.0003	8.581.0022
power supply	220/240 V 50/60Hz	24V (battery charger included)	24V (batteries and charger included)	24V (Li-ion battery and charger included)
scrubbing/squeegee width	360/460 mm	360/460 mm	360/460 mm	380/460 mm
max working capacity	1260 m ² /h	1260 m ² /h	1260 m ² /h	1350 m²/h
solution tank capacity	15 l/3.96 gal	15 l/3.96 gal	15 l/3.96 gal	15 l/3.96 gal
recovery tank capacity	16 l/4.23 gal	16 l/4.23 gal	16 l/4.23 gal	16 l/4.23 gal
traction	mechanical	mechanical	mechanical	mechanical
RPM/pressure on the brush	130/18 kg/40 lbs	160/27 kg/60 lbs	160/27 kg/60 lbs	160/27 kg/60 lbs
brush motor power	300 W	400 W	400 W	400 W
detergent solution system	solenoid valve	solenoid valve	solenoid valve	solenoid valve
depression/vacuum motor	850 mmH ₂ O/350 W	850 mmH ₂ O/270 W	850 mmH ₂ O/270 W	850 mmH ₂ O/270 W
dimensions/weight	98x47x99 cm/57 kg	98x47x99 cm/46 kg	98x47x99 cm/70 kg	98x47x99 cm/63 kg

WALK BEHIND



On/off switch protecting unintentional use. Protection against overloads, battery discharge abuse (DC only) and undesired run.

Convenient one switch maintenance over the brush. Eco Energy setting for extensive working time and extremely quite operations (DC only).

Accessible on-board charger (DC only, when provided), far away from sprays. Time saving convenient foot operating squeegee lift. Handle can be easily adjusted to fit comfort of operators even

in narrow spaces.





Easy access and handling to clean recovery tank and floater. Less downtimes due to simple maintenance and construction Great visibility and cleaning capability on hard to reach edges on both sides of the brush.

Extensive squeegee spin for easy blade replacement and perfect suction even on corners Easy setting and automatic solution release to save chemical and fit different floor conditions. High stability and capability to overtake small steps.



OPTIONAL



- 5.511.2214 Tynex brush Ø 360 mm-14"
- 5.511.2215 PP 0,3 brush Ø 360 mm-14"
- 5.511.2216 PES brush Ø 360 mm - 14"
- 5.511.2264 Tynex brush Ø 380 mm-15"
- 5.511.2265 PP 0,3 brush Ø 380 mm-15"
- 5.511.2266 PES brush Ø 380 mm - 15"



- 4.508.1058 Polyurethane front blade L.537
- 4.508.1059 Polyurethane rear blade L.590



• 5.511.2217 EWU pad driver Ø 360 mm-14"



- 6.508.0143
- Abrasive pad Ø 381 mm-15"
- beige
- 6.508.0144
- Abrasive pad Ø 381 mm-15"
- 6.508.0141
- Abrasive pad Ø 381 mm-15"
- black



4.512.0068 Extension electric cord 15 m with Schuko plug (Dart 36 E)