

Windy 378 PF



Equipped with:

- 3 high efficiency by pass motors.
- Suction system with by-pass cooling.
- Filter cleaning system.
- Plastic tank (PP).
- Shock proof trolley.
- Liquid float valve.
- Static electric shock inhibitor.
- Drain hose system.
- 7,5 m power cable.
- Traceless wheels.
- Accessories Ø 40.
- Handy accessory holder.

Windy 378 PF	
code	8.256.0002
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W High efficiency motor.
column depression	22 kPa/2200 mmH ₂ O
air suction	195 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension/weight	62x51x99 cm/23,5 kg

STANDARD EQUIPMENT

- 5.209.0021 Hose 2,5 m 
- 6.205.0126 
- 3.754.0048 
- 3.754.0049 
- 3.754.0083 400 mm 
- 3.754.0084 
- 3.754.0085 
- 5.509.2176 Cloth filter 

Optional:

- 5.212.0022 Paper collector filter set - 10 pcs
- 5.509.1405 Cloth filter for fine dust
 - 5.212.0093 Nylon filter
 - 5.212.0021 Washable filter
 - 5.212.0034 Hepa filter