# LEVEL CONTROL

## Technical datasheet

Technical datasheet No: FUEL-Mano-Clock Multi

Product code: 308 059 / 308 061

### Designation

Universal float gauge for indoor and outdoor tanks. Intended for use with open vented stationary tanks. Infinitely adjustable to the desired height of tank, and can therefore be fitted to all tanks.

### Application

Suitable for use with Fuel oil/diesel fuel (EN 590), Biofuel FAME (EN 14213), Biodiesel FAME (EN 14214) and motor oil.

#### **Function**

The movements of the floater are transmitted by a line to the measuring mechanism inside the meter house. The measuring mechanism consists of a spring-loaded winding drum actuating the pointer needle by means of a gear drive.

### + Product

- Suitable for indoor and outdoor tanks
- Big meter house  $\emptyset$  110 mm in high quality UV-resistant plastic (ASA/SAN). UV-tested according to EN ISO 4892-1.
- Pressure-tight meter house design prevents the spread of oil odour indoors.
- Corrosion-resistant measuring mechanism in acetal plastic (POM) and spring motor made of stainless steel.
- Durable float made of acetal plastic (POM).
- Easy and quick installation
- **Economical**
- Can be easily adjusted to the desired tank height by using a screwdriver.

## Technical specifications

Operating temperature: -30°C / +50°C Float diameter: Ø 36 mm Meter house: Ø 110 mm Mounting position: vertical

0/200 cm or 0/250 cm Measuring range: ±3% FS (of full scale) Measuring accuracy: Connection: G1 1/2" M BSP

## Options / accessories

	Weight Kg	Part no.
Plastic reducer / adapter G2" M x 1" 1/2 F	0,02	104 010
Plastic reducer / adapter G2"M x 1" F	0,02	107 089
Plastic reducer / adapter G1" . M x 1" F	0,01	107 088

### Warranty

12 months provided fitting and operating instructions are observed

12 months provided fitting and operating matractions are observed.		
	Weight Kg	Part no.
Float gauge Mano-Clock Multi 200 cm (Adjustable for tank height 100-200 cm)	0,30	308 059
Float gauge Mano-Clock Multi 250 cm (Adjustable for tank height 150-250 cm)	0,30	308 061



Date: 10/2021 Version: original







Page: 1/1


















Fully adjustable

NOTE: Not for use with tanks containing gasoline, ethanol, etc. or pressurized tanks. Not intended for use as an overfill prevention device. All specifications are subject to change without prior notice. Directives and Regulations may vary from country to country.



Tel.: +33(0)1 60 05 18 53 Fax: +33(0)1 60 17 58 39 info@selfclimat-morvan.com VAT No. FR 25 698 202 868 www.selfclimat-morvan.com